



**camstage**

31 Hedley Road  
St Albans  
Hertfordshire  
AL1 5JR

**t:** +44 (0) 1727 830 151  
**f:** +44 (0) 1727 855 993  
**e:** info@camstage.com  
**w:** www.camstage.com

## CSCC-2005

The Camstage curtain controller is a general all purpose single or double line winding unit. This unit can also be used in a variety of ways including moving masking controlling.

### **Construction:**

Type	Powder coated steel work chassis
Mounting	Supplied with four mounting holes
Dimensions	H315mm x W400mm x D445mm

### **Motor:**

Type	Lenze MDC71C4 motor (Further information is available on request)
Operation	230v Single Phase ½ hp 1380 rpm

### **Drum:**

Construction	Aluminum
Drum Guard	360° Adjustable cable access
Size	220 mm
Turns	26
Travel	0.2m - 17.9m
Cable size	2mm or 3mm

### **Gear Box:**

Ratio	63 – 1
Type	Worm Drive

### **Limits:**

Type	TER MF 2C
Ratio	50 – 1

### **Operation:**

Type	Camstage 2005 24v Relay circuit switching board
Stops	2
Controls	Stop, Common, Open, Close
Remote Port	Yes

### **Optional:**

Remote Buttons	Stop, Open, Close
----------------	-------------------



The curtain controller provides a long and troubled free service but should be regularly checked to make sure no deformation has occurred.

The limits should never be exceeded. The building support structure must be of similar or greater load bearing capacity. After installation the complete unit must be inspected and tested in line with the local and national regulations. Fasteners are not supplied unless specified. The controller must be mounted on a flat horizontal or a flat vertical surface with drum access horizontal.

In the interest in product enhancements STAGE SHOP LTD reserves the right to introduce modifications or alterations without prior notice.